



QS1080IRCI

High Definition Digital Satellite Receiver

Embedded Irdeto Plus 2 Common Interface Slots

HD1 Approved

General Specifications

Input Frequency	950~2150 Mhz
Demodulator	QPSK
Chipset	Broadcom® BCM7035
Flash	2 MB
SDRAM	64 MB
EEPROM	32 KB
CA	Irdeto Softcell
Loader	Irdeto Loader
Video Decoder	MPEG 2 MP@HL, MP@ML
Output Selection	DVI/RGBHV/YPbPr/SVHS/Composite
Output Format	1080i/720P/576P/576i
Aspect Ratio	16:9, 4:3 selectable
Audio Decoder	Dolby Digital, MPEG layer I & II
Analog Output	Dolby Down-mix, RCA
Digital Output (SPDIF)	PCM or Dolby Digital, Optical
Smart Card Slot	1
PCMCIA Slot	2
Power	100~240 VAC, 50~60 Hz
Dimension	360 * 250 * 65 (mm)
Weight	3.5 Kg

FEATURES:

- Two Common Interfaces
- Enable to Decode QPSK Transmission
- HDTV and SDTV Format Support
- Teletext
- AUX in for DVD/VCD Composite Input

- Output Format 1080i, 720P, 576P and 576i
- User-Friendly OSD and Operation
- Favorite Channel Selection
- S/W Upgradeable through RS-232 / OTA
- Parental Guide and

- Rating Control
- Picture in Picture (PIP) Support
- Electronic Program Guide (EPG)
- DiSEqC 1.0&1.2
- Dolby Digital, MPEG Layer I & II
- HD1 Approved